



PRODUCT RANGE COMPARISON CHART | FOLDING DOORS



PRODUCT	V2	ALUMINUM THERMALLY CONTROLLED	ALUMINUM	CONTEMPORARY CLAD	ALUMINUM WOOD	VINYL	WOOD
STYLE	CONTEMPORARY	CONTEMPORARY	CONTEMPORARY	CONTEMPORARY TO TRADITIONAL	TRADITIONAL	CONTEMPORARY TO TRADITIONAL	TRADITIONAL TO CONTEMPORARY
PRICING	\$\$\$	\$\$	\$	\$\$	\$\$	\$	\$
STILE & RAIL PROFILE	2 1/8"	2 15/16"	2 15/16"	2 15/16"	3 5/8"	2 15/16"	3 5/8"
LOCK TYPE	AUTOMATIC LOCKING SYSTEM	TWIN BOLT LOCKING SYSTEM	TWIN BOLT LOCKING SYSTEM	TWIN BOLT LOCKING SYSTEM	TWIN BOLT LOCKING SYSTEM	TWIN BOLT LOCKING SYSTEM	FLUSH BOLT LOCKING SYSTEM
HINGE TYPE	HIDDEN HINGES & CONCEALED HANDLES	SURFACE MOUNTED INTERIOR HINGES & PULL HANDLES	SURFACE MOUNTED INTERIOR HINGES & PULL HANDLES	SURFACE MOUNTED INTERIOR HINGES & PULL HANDLES	SURFACE MOUNTED INTERIOR HINGES & PULL HANDLES	SURFACE MOUNTED INTERIOR HINGES & PULL HANDLES	SURFACE MOUNTED INTERIOR HINGES & PULL HANDLES
PANEL CONSTRUCTION	ALUMINUM W/ THERMALLY EFFICIENT CORE. WOOD INTERIOR OPTION AVAILABLE	ALUMINUM W/ THERMALLY EFFICIENT CORE	ALUMINUM	ENGINEERED WOOD CORE W/ EXTERIOR ALUMINUM	ALUMINUM WITH SOLID WOOD INTERIOR	VINYL	ENGINEERED WOOD CORE
SIMULATED DIVIDING LITES (SDLs)	7/8" CONTEMPORARY	1" CONTEMPORARY	1" CONTEMPORARY	1" CONTEMPORARY OR TRADITIONAL	1" CONTEMPORARY OR TRADITIONAL	-	1" TRADITIONAL
ENERGY EFFICIENCY	BEST	BETTER	GOOD	BEST	BETTER	BETTER	BEST
U-VALUE LOW-E-366 ARGON*	.36	.37	.48	.31	.38	.34	.30
WOOD SPECIES	VG FIR OR SAPELE MAHOGANY	-	-	VG FIR OR SAPELE MAHOGANY	VG FIR OR SAPELE MAHOGANY	-	VG FIR OR SAPELE MAHOGANY
STOCK FINISHES	CLEAR ANODIZED BRONZE ANODIZED WHITE PAINT BRONZE PAINT SHADOW BLACK PAINT	CLEAR ANODIZED BRONZE ANODIZED WHITE PAINT (SPLIT FINISHES AVAILABLE)	CLEAR ANODIZED BRONZE ANODIZED WHITE PAINT (SPLIT FINISHES AVAILABLE)	CLEAR ANODIZED BRONZE ANODIZED WHITE PAINT BRONZE PAINT SHADOW BLACK PAINT	WHITE PAINT BRONZE PAINT SHADOW BLACK PAINT	WHITE VINYL TAN VINYL	-

*THE ABOVE TABLE SHOULD SERVE AS A GENERAL REFERENCE FOR THERMAL PERFORMANCE VALUES. PLEASE NOTE THERMAL PERFORMANCE VALUES MAY VARY BASED ON THE ATTRIBUTES OF A GIVEN DOOR SYSTEM.

*PERFORMANCE RESULTS BASED ON OUTSWING WEATHER RESISTANT SILL.